TruSeal

Acrylic Floor Sealer and Base Coat



Product Features

- Protects from stains caused by matting, tar, and rust. Protects against deterioration caused by years of stripping operations.
- Increases clarity and gloss of subsequently applied floor finishes.
- Semi-permanent. Eliminates need to seal after every stripping cycle.
- Levels and dries streak-free in 30 minutes.

Description

TRUSEAL is a semi-permanent floor sealer that resists the action of normal strippers and the mechanical action of floor machines. It can be applied over resilient and non-resilient substrates and one or two coats will effectively seal porous floors. Superior holdout allows floor finish to build gloss without being absorbed into the substrate.

Product Properties

Appearance Opaque white liquid

Specific Gravity, at 20°C 0.95-1.05 kg/L

Flash Point none
Freeze/Thaw Stability Protect
pH, (concentrate) 6-8

Scent Characteristic Solubility Miscible

Shelf Life 1 year minimum

Directions for Use

PREPARATION: If floor requires stripping use recommended stripper as directed. If floor is in good condition, ensure floor is thoroughly clean and dry before applying TRUSEAL.

APPLICATION: If floor is in good condition, ensure floor is thoroughly clean and dry. Apply 1-2 thin uniform coats with a finish mop of application machine. Drying time is about 15-30 minutes. Recoat time is a minimum of 1 hour. If the floor is porous, extend recoat time to well beyond 1 hour.

Available Packaging

2 x 10 L Case 20 L Pail

