Voodoo

Super-performance foaming cleaner & degreaser. All water compatible.



Product Features

- Fast and effective cleaning performance that surpasses all other conventional vehicle cleaning products
- Compatible with both hard and soft water
- Risnses without leaving behind residues or films
- High foaming formulation allows extended contact time and application via foamer (air or airless)
- Formulated to provide a spot-free and streak-free shine
- Softens, lifts, and helps remove insect residues and designed to penetrate and remove most traffic films
- Solvent-free, VOC-free and does not have a flash point
- Designed for use on most surfaces when properly diluted, including aluminum, chrome, glass, plastic, and painted finishes

Description

VOODOO is a non-caustic, high foaming detergent that exhibits unrivaled cleaning performance. Ideal for touchless washing of cars, trucks, trailers, tractors, equipment, and other hard-to-clean surfaces such as rubber and vinyl. This fast-acting super cleaner rinses completely residue-free, is safe on most surfaces (including aluminum) and utilizes special built-in water softeners for amazing results in both hard or soft water. VOODOO delivers powerful touchless cleaning and spotless, high-gloss results. This product is ideal for use in touchless and wand wash operations, commercial car and truck washes, and through foamers in industrial wash bays.

This product is uniquely effective in removing road/traffic films, general vehicle soils, as well as insect residue. VOODOO's unique surfactants synergistically work to help lift dirt away and leave a clean and shiny vehicle. Using VOODOO will contribute to enhanced shine and spot-free rinsing without the aid of a separate drying aid.

Directions For Use

For most pressure wash and vehicle wash applications dilute VOODOO between 1:80 and 1:400 with water and apply to surface via suitable foam sprayer or via high pressure wand wash. Let stand for up to 10 minutes depending on the severity of the cleaning task. Some agitation may be required, and product should be rinsed prior to drying.

For high pressure operations dilution rates of up to 1:400 are typically effective. Use these ratios as a starting point to determine the ideal feed ratio to produce the desired results. Dilution ratios may also vary depending on water conditions and the nature of soil. If possible, use warm to hot water (40-70 C) when diluting this product as the higher temperature will enhance the performance of the product.

RINSE THOROUGHLY FROM ALL SURFACES

Product Properties

Appearance green liquid
Odor virtually odorless

Foam color white

Specific Gravity, at 20°C 1.10-1.20 kg/L

Flash Point none
Freeze Point 0°C
pH, 1% solution, at 20°C 9-12

Shelf Life 1 year minimum

Applications include

- General purpose pressure washing & foam cleaning
- Commercial Truck and Vehicle Washes
- Traffic film removal
- Cleaning rubber and vinyl
- Removal of greases and oils

Available Packaging

4x4L cases205 L drums20L pails1000 L totes

55L drums

